

Single Clapper Siamese Connections

Features:

- single swing clapper with (2) pin lug swivel inlets
- provides 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet)
- design provides unobstructed waterway
- exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes
- branding: Auto-Spkr
- finishes: -P polished or -C polished chrome plated
- maximum operating pressure: **250 PSI** at 70°F (21°C)



back outlet
21-201

Feature:

- U/L listed and FM approved




(2) Inlets Female	Outlet Female NPT	Cast Brass Part #	Price	Wt. Lbs.
2½" NST (NH)	4"	SCS4025F ³	\$539.25	11.6
2½" NYFD	4"	SCS4025NYFD	539.25	19.0
2½" CT	4"	SCS4025 ¹	POR	19.0
2½" NST (NH)	4"	ISCS4025F ³	238.35	7.5
---	4"	ISCS4025-BODY ²	POR	7.0

¹ Customer Thread (*must specify*) refer to legend on page 566

² replacement swivels can be ordered on page 566

³ imported



Dimensions

Size	A	B	C
4" x 2½" x 2½"	5⅝"	9"	6-1/16"

- dimensions match SCS4025F-D and SCS4025NYFD



bottom outlet
21-202

Feature:

- U/L listed




(2) Inlets Female	Outlet Female NPT	Cast Brass Part #	Price	Wt. Lbs.
2½" NST (NH)	4"	90SCS4025F ³	\$656.40	11.6
2½" NST (NH)	4"	90SCS4025F-SP	656.40	19.0
2½" NYFD	4"	90SCS4025NYFD	656.40	19.0
2½" CT	4"	90SCS4025 ¹	POR	7.5
2½" NST (NH)	4"	90ISCS4025F ³	296.55	7.0
---	4"	90ISCS4025-BODY ²	POR	---

¹ Customer Thread (*must specify*) refer to legend on page 566

² swivels can be ordered on page 566

³ imported



Dimensions

Size	A	B
4" x 2½" x 2½"	6⅞"	9⅞"

- dimensions match 90SCS4025F-D, 90SCS4025F-SP, and 90SCS4025NYFD

P