

### Turbo Nozzles

**Features**

- 20° spray angle
- Ceramic orifice

**Specification**

- Maximum temperature: 212°F (100°C)

Nozzle Size	Description	Orifice	Maximum Working PSI	Part #
4.0	1/4" female inlet	1.30 mm	3,700	AL-TPR25-30
6.0	1/4" female inlet	1.50 mm	3,700	AL-TPR25-50
7.0	1/4" female inlet	1.70 mm	3,700	AL-TPR25-70
4.0	1/4" female inlet	1.30 mm	5,075	AL-TPR35-30
6	1/4" female inlet	1.50 mm	5,075	AL-TPR35-50
7	1/4" female inlet	1.70 mm	5,075	AL-TPR35-70



### Nozzle Holders

**Specification**

- Maximum temperature: 320°F (160°C)

Description	Flow (GPM)	Working PSI	Part #
adjustable high/low nozzle holder with nozzle protector, 1/4" female inlet and outlet	8	3,650	AL414
change over nozzle, 1/4" female inlet, 2 each 1/4" female outlets	8	2,900	AL416



AL414



AL416



### Inlet Filter for Turbo Nozzles

**Features**

- 1/4" female inlet, 1/4" male outlet
- 100 mesh filter

**Specification**

- Maximum temperature: 212°F (100°C)

Description	Flow (GPM)	Working PSI	Part #
stainless steel, inlet water filter	8	5,000	AR3500



### Water Broom

**Feature**

- 1/4" quick connect plug

**Specification**

- Working PSI: 4,000 PSI

Description	Length	Stainless Steel Part #
4-nozzle broom	16"	AR-BROOM16

