


Nitrile Washdown Hose

Application

- Ideal for industrial, agricultural, and construction washdown and discharge applications, not for fire fighting 

Feature

- Resistant to weather and abrasion

Uncoupled



Size	Color	Bowl	Length	Working Pressure (PSI)	Part #	
1"	black	1-1/4"	50'	200	WDH10BK50UC	
			100'		WDH10BK100UC	
	yellow	1-1/4"	100'		WDH10Y100UC	
	blue	1-1/4"	100'		WDH10BL100UC	
1-1/2"	black	1-13/16"	50'		WDH15BK50UC	
			100'		WDH15BK100UC	
2"	black	2-5/16"	50'		WDH20BK50UC	
			100'		WDH20BK100UC	
2-1/2"	black	2-13/16"	50'		WDH25BK50UC	
			100'		WDH25BK100UC	
3"	black	3-3/8"	50'		150	WDH30BK50UC
			100'			WDH30BK100UC
4"	black	4-3/8"	50'	WDH40BK50UC		
			100'	WDH40BK100UC		
6"	black	6-3/8"	50'	WDH60BK50UC		
			100'	WDH60BK100UC		

Dixon® PVC Flexible Suction Hose

Couplings with PVC Flexible Suction Hose



cam & groove x cam & groove



female L/H x male R/L



storz x storz

Size	Length	Thread	Female L/H x Male Part #	Female R/L x Male Part #	Storz x Storz Part #	Cam & Groove x Cam & Groove Part #
2-1/2"	10'	NST	FSH-9682-000	FSH-9682-050	FSH-9682-020	---
		BAT	FSH-9682-000B	FSH-9682-050B		
		CSA	FSH-9682-000C	FSH-9682-050C		
		WCT	FSH-9682-000W	FSH-9682-050W		
		NS1	FSH-9682-000NS	FSH-9682-050NS		
		QST	FSH-9682-000Q	FSH-9682-050Q		
3"	10'	NH	FSH-9682-100	FSH-9682-150	---	FSH-9682-130
4"			FSH-9682-200	FSH-9682-250	FSH-9682-220	FSH-9682-230
4-1/2"			FSH-9682-300	FSH-9682-350	---	---
5"			FSH-9682-400	FSH-9682-450	---	---
6"			FSH-9682-500	FSH-9682-550	---	FSH-9682-530